

A standard linear barcode is positioned vertically on the right side of the page. It consists of vertical black bars of varying widths on a white background.

ISSUE CLASSIFICATION

BEST AVAILABLE COPY

PATENT NUMBER

U.S. UTILITY Patent Application

O.I.P.E.	PATENT DATE
SCANNED <i>SS</i>	Q.A. <i>R</i>

APPLICATION NO.	CONT/PRIOR	CLASS	SUBCLASS	ART UNIT	EXAMINER
09/685196		375	343	2631	CHAN RUPERT

APPLICANTS

Timothy Miller
John McCorkle

Ultra-wide bandwidth system and method for fast synchronization using multiple detection arms

PTO-2040
12/99

ISSUING CLASSIFICATION

TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.					
<input checked="" type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent No. _____	(Assistant Examiner)		(Date)	NOTICE OF ALLOWANCE MAILED	
				ISSUE FEE	
	(Primary Examiner)		(Date)	Amount Due	Date Paid
<input type="checkbox"/> The terminal _____ months of	ISSUE BATCH NUMBER				

WARNING:

The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code, Title 35, Sections 122, 181 and 368. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-436A
(Rev. 6/99)

FILED WITH: DISK (CRF) FICHE CD-ROM
(Attached in pocket on right inside flap)

(FACE)